

## TAPS F-CONNECTION 2400 MHz FOR SAT-IF

- For indoor usage
- Connection: F-female
- Frequency range 5-2400 MHz
- Die-cast housing with earth bonding
- Screening factor > 100 dB, CLASS A
- Hum-suppression
- DC-power pass at trunk line max. 1 A

Type		STA 0124-10	STA 0224-10	STA 0424-10
Item No.		57000995	57000996	57000997
Frequency range	MHz	5 – 2400	5 – 2400	5 – 2400
Taps		1	2	4
Tap loss	± 1.0 dB	10	11	11.5
Insertion loss	dB			
5-40 MHz		1.5	4.5	5.0
41-1000 MHz		1.8	3.2	5.0
1001-1750 MHz		2.2	3.8	5.2
1751-2400 MHz		2.8	4.2	5.5
Directional isolation	dB	> 23	> 26	> 20
Port isolation TAP-TAP	dB	-	> 26	> 18
Return loss >40 MHz	dB	> 12	> 12	> 9
Connector		F-female	F-female	F-female
Dimensions	mm	52 x 51 x 17	74 x 51 x 17	74 x 63 x 17
Weight	kg	0.05	0.06	0.09

## SPLITTER F-CONNECTION 2400 MHz FOR SAT-IF

- Frequency range 5-2400 MHz
- Power pass all outlets, diode isolated



KLASSE  
**A**  
CLASS

Type		VT 0224	VT 0324	VT 0424	VT 0624	VT 0824
Item No.		10161293	10161294	10161295	10161296	10161297
Frequency range	MHz	5 - 2400	5 - 2400	5 - 2400	5 - 2400	5 - 2400
Outputs		2	3	4	6	8
Through loss	dB					
5-1000 MHz	± 0.5 dB	4.5	7.5	9.0	11.5	12.5
1001-1700 MHz		6.0	8.8	10.0	13.5	15.2
1751-2400 MHz		6.5	10.5	11.0	16.0	17.5
Isolation	dB	> 19	> 20	> 21	> 21	> 21
Return loss > 40 MHz	dB	> 9	> 11	> 11	> 11	> 11
Dimensions	mm	52 x 51 x 17	74 x 51 x 17	74 x 51 x 17	118 x 60 x 17	118 x 60 x 17
Weight	kg	0.05	0.06	0.07	0.13	0.14