

TWIN-WALL OUTLET SAT-IF

- Twin-wall outlet for 2-wire-SAT-IF application
- With DC pass
- Including cover plate and frame



| Type | Frequency range | STD 2400 |
|-----------------------|-----------------|---|
| Item No. | | 10161174 |
| | | |
| Description | | Terminal-twin wall outlet |
| Attenuation | | |
| TV OUT (IEC-male) | dB | 85-862 MHz |
| RF OUT (IEC-female) | dB | 87.5-862 MHz |
| 2x SAT OUT (F-female) | dB | 950-2200 MHz |
| DC pass | | 12 V = max. 500 mA (over SAT-IF-connectors) |

ACCESSOIRES FOR ANTENNA WALL OUTLETS

| Type | AD 3 SET | AD 3-2 | AP 1 |
|-------------|--|---|--------------------|
| | | | |
| Item No. | 57001452 | 57004041 | 10161348 |
| Description | Set with cover plate (2 parts) and frame for 3-hole outlets (pure white) | cover plate 2 part for 3-hole outlets (pure white) | Frame (pure white) |
| Dimensions | mm 76 x 76 x 8 / 76 x 76 x 32 | 76 x 76 x 8 | 76 x 76 x 32 |

| Type | R 75 | R 75 DC |
|-----------------|-----------------------------|-----------------------------------|
| | | |
| Item No. | 57000813 | 57000990 |
| Description | Terminal resistor | Terminal resistor DC isolated |
| Frequency range | MHz 0 – 2200 | 10 – 2200 |
| Load | 75 Ohm | 75 Ohm |
| Application | For DC isolated walloutlets | For SAT-wall outlets with DC pass |