

## PARABOLIC OFFSET REFLECTORS

- || 10.7–12.75 GHz (KU Band)
- || High stability –
  - 40 mm die-cast feed mount (part of shipment) and
  - Mast holder with wing screws
- || Corrosion-resistant – Aluminium reflector, hot-dip galvanized mast bracket
- || Appealing design
  - available in three colors: white, graphite, brick red
  - integrated cable duct
  - Back bracket in reflector color
- || Also available in PU:10, bulk (On request)
- || Also available in heatable version (On request)



Type		SAT 75	SAT 85	SAT 100
Color / Item No.	white	57001277	57001280	
	graphite	57001278	57001281	57001284
	brick red	57001279	57001282	57001285
Reflector-Ø	m	0.75	0.85	1.0
Gain	dB	37.3	38.3	40
Half-value aperture	°	2.4	2.1	1.8
Mount for mast Ø	mm	40 - 80	40 - 80	40 - 80
Adjustment range, elevation	°	10 - 40	10 - 40	10 - 40
Wind load	N	480	600	800
Width x height	cm	75 x 80	85 x 90	94 x 101
Dimensions	cm	76 x 86 x 20	90 x 86 x 20	116 x 102 x 25
Weight	kg	7.0	11.0	11.5



### High stability

- || Solid material profiles and hexagonal clamping nuts
- || One-piece construction of support arm and LNB mount
- || Wing nuts for assembly without tools



### Protected cable duct

- || Secure and clean cabling on support arm