

GALVANIC ISOLATOR

- To avoid offset current between different electrical potentials
- Capacitors for galvanic isolation of IN- and outputs
- Immunity to surge voltages up to 1 kV
- No DELTA Electronics labelling



Type		TRISX-1002
Item No.		57004079
Frequency range	MHz	5 - 1218
Through loss	dB	0.4 ... 0.7
Linearity	dB	± 0.5
Immunity to surge voltages	kV	1 (between in- and output potentials)
Dimensions	mm	60 x 30 x 38

TRIS HOUSING

- TRIS-housing for the galvanic isolator
- Suitable for TRIS-1002 AEN & TRISX-1002



Type		TRIS-Housing
Item No.		57001201
Dimensions	mm	85 x 85 x 40

FIX ATTENUATOR

- Small housing, 40 x Ø 11 mm
- Connector: F-female and F-male
- CLASS A



Type	FR 3-3	FR 3-6	FR 3-10	
Item No.	57001154	57001155	57001156	
Frequency range	MHz	5 - 2400	5 - 2400	
Attenuation	dB	3	6	10
Remarks	DC-Pass	DC-Pass	DC-Pass	

Type	FR 1-3	FR 1-6	FR 1-10	
Item No.	57002351	57002352	57002353	
Frequency range	MHz	5 - 1218	5 - 1218	
Attenuation	dB	3	6	10