

## AMPLIFIER

- ▮ Separate adjustment of gain and slope for each input
- ▮ AGC & ASC (WBV 220 Pro)
- ▮ Plug'n'Play ( WBV 220 Pro)
- ▮ Output level selectable ( WBV 220 Pro)
- ▮ Two trunk lines
- ▮ Remote or direct powered \*



Type	WBV 230		WBV 220 Pro	
Item No.	57003181		57004068	
Inputs SAT	2		2	
Frequency range SAT	MHz	290...2340	290...2340	
Outputs trunk line	2		2	
Input level	dB $\mu$ V	57-77	50-70	57-77
Output level	dB $\mu$ V	110	70 (AGC regulated)	77 (AGC regulated)
Gain	dB	30	15	
Slope control	dB	manuell (0...15)	15 (ASC)	
Gain adjustment range	dB	15...30	20 (ASC)	
Power consumption	mA	150 @ 20 V	150 @ 20 V	
Operating temperature	°C	-25...+60	-25...+60	
Dimensions	mm	115 x 130 x 50	115 x 130 x 50	
Weight	g	0.235	0.235	

\* Power supply from externally with an external plug-in power supply (e.g. NT 20-1.2F Item No. 57004430) or by remote feeding through trunk lines.