

WIDEBAND LNB


- Weatherproof cap extendable
- Very low noise figure
- Compact size



Type		UCW 12
Item No.		57003268
Inputs		1
Input frequency	MHz	10700...12750
Outputs		2 (H/V)
Output frequency	MHz	290...2340
LO frequency	MHz	10410
Conversion gain	dB	55
Noise figure	dB	0.7
Isolation	dB	25
Output power	dBm	-25
Power supply	VDC	9...20
Power consumption	mA	150
Operating temperature	°C	-40 ... + 60
LNB Installation dimensions	∅ mm	40
Dimensions	mm	90 x 80 x 40

SAT-IF INLINE AMPLIFIER

- Super wideband amplifier for terrestrial and SAT range
- Frequency range 47 up to 2300 MHz
- Remote feeding via coaxial RF connector
- DC-pass for LNB remote feeding
- Die-cast enclosure Class A
- Suitable for Unicable



Type		NV 1624 D
Item No.		57002025
Frequency range	MHz	47 ... 2300
Inputs		1 (F)
Outputs		1 (F)
Gain 40 MHz	dB	16
Gain 950 / 1750 / 2300 MHz	dB	18 / 20 / 24
Output level: SAT 35 dB IMA ₃	dBμV	110
TERR 60 dB IMA ₃	dBμV	105
Remote feeding voltage	V	11 ... 20 (bi-directional)
Power consumption	mA	60
Dimensions	mm	45 x 24 x 24
Weight	kg	0.04