




CABLE SIMULATOR PADS

- For LHD / NVD amplifier
- Frequency range 47-1218 MHz
- 5.6 mm thick

Type	CSP 12045	CSP 12060	CSP 12075	CSP 12090	CSP 12105	CSP 12180
Item No.	57003641 (PU 10)	57003642 (PU 10)	57003643 (PU 10)	57003644 (PU 10)	57003645 (PU 10)	57004446 (PU 10)
EQ values db	4.5	6.0	7.5	9.0	10.5	18
47 - 1218 MHz db	3.7	4.9	6.2	7.4	8.6	14.8
47 - 1000 MHz db	3.2	4.3	5.4	6.4	7.5	12.8
47 - 870 MHz db	2.9	3.9	4.8	5.8	6.8	11.6
Tolerance eq-val. max. db	+/- 0.5					
Flatness db	+/- 0.2				+/- 0.25	
Insertion loss db	≤ 1					
Return loss db	≥ 18				≥ 17	
Impedance Ω	75					

Length 25.4 mm (1")

FITTINGS PG 11

Type	PG11m-Ff	PG11m-IECf	PG11m-3,5/12f	PG11m 3,5/12f
				
Item No.	57001082	10161203	57001141	57001291
Description	PG 11 - Adapter PG 11 / F-female	PG 11 - Adapter PG 11 / IEC-female	PG 11 - Adapter PG 11 / 3.5 / 12 female	PG 11 - Adapter PG 11 / 3.5 / 12 female
Connector Pin length	47 mm	17 mm	47 mm	17 mm

Type	PG 11m-5/8f	PG 11 PC
		
Item No.	10161204	10161205
Description	PG 11 - Reduction ring PG 11 / 5 / 8"	PG 11 Blind cap