

OPTICAL RECEIVER WITH AGC

- Optical multiple Receiver with automatic gain control (AGC)
- LED-indication for signal receive
- Compact design
- DC Supply on all SAT outputs
- Wide range of optical input



Type		OR 15 AGC	OR 25 AGC	OR 35 AGC	OR 35-2 AGC	OR 55 AGC
Item-No.		57004586	57004211	57004212	57004466	57004465
Optical input		1 <i>On request</i>				
RF outputs		1	2	3	3	5
Optical wavelengths	nm	1550	1310, 1330	1310, 1330, 1550	1350, 1370, 1550	1310,1330,1350,1370,1550
Frequency range	MHz	5...2400				
Optical input level	dBm	-15 to + 4				
AGC RF output level	dB μ V	80				
Signal indication		Green LED per wavelength				
Return loss	dB	-10				
Optical connector		SC / APC				
RF connector		F-type female (75 Ohms)				
Power consumption	W	2		3		4
DC supply via RF outputs	V	12 to 20				
DC supply indication		Green LED				
Operation temperature range	$^{\circ}$ C	-20 to +55				
Dimensions	mm	40 x 125 x 50	40 x 125 x 50	60 x 125 x 50		100 x 125 x 50
Weight	kg	0.100	0.110	0.165		0.275